



## Build with Confidence Use the right fastener for the job

TrueSpec® Nail Identification System ensures the correct fastener is used in the intended application by color coding and numbering of the nail head for easy identification.

Once driven into the material, the nail head color identifies the length, and the shank diameter is identified by a number stamped on the head. The simple nail identification chart confirms TrueSpec® as the easiest and most complete head identification system available. ZincGard® Galvanized is Tree Island's high grade galvanizing process that delivers maximum corrosion resistance.

**ZincGard® Hot Dipped Galvanized** offers more protection than competitive fasteners for exterior and ground level exposure applications that require galvanized nails. Our ZincGard® coating meets or exceeds ASTM A153 Class D standards and resists rust even when a portion of the finish is damaged, unlike other finishes such as "electroplating" and "paint type" coatings.

- Color designates nail length
- Number indicates the shank diameter
- Threaded nails, such as ring/screw (deformed shank), are identified with a lower case "r".
- If the nail is used in hardware application such as fastening connectors, an "H" is placed after the number.
- A combination of alpha and numeric characters indicate nail diameter and length for ZincGard® hot galvanized nails.

Available in: 250, 800, 2000, 3000, 4000, and 5000 count cartons.



### Meets

- ICC CERTIFIED ESR 1768
- LOS ANGELES 25895
- ASTM F1667, A153 Class D (for hot galvanized), and C514 (stainless steel)

### TRUESPEC® NAIL IDENTIFICATION CHART

Diameter	Indicator Smooth Shank	HDG Indicator Smooth Shank	HDG Indicator Ring Shank	Length	Indicator Smooth Shank	HDG Indicator
0.113"	1	1	T	1 1/2"	Purple	A
0.120"	2	2	U	2 1/8"	Pink	B
0.131"	3	3	W	2 1/4"	Brown	C
0.135"	5	5	X	2 3/8"	Green	D
0.148"	4	4	Y	2 1/2"	Blue	E
0.162"	6	6	Z	3"	White	F
H - Stamped on Head = Hardware Nail r - Stamped on Head = Ring or Screw Shank (smooth only) NOTE: HDG stands for Hot Dipped Galvanized				3 1/4"	Black	J
				3 1/2"	Orange	K